



# PKA-SERIES Wall-Mounted

## COOLING ONLY



Indoor unit  
PKA-A12/18HA



Indoor unit  
PKA-A24/30/36KA



Slim Smart Remote



Outdoor unit  
PUY-A12/18NHA3



Outdoor unit  
PUY-A24/30/36NHA3

- Variable Compressor Speed Inverter Technology
- Ozone-Friendly R-410A Refrigerant
- Significant Energy Savings up to 30%
- Super-Quiet Technology
- Easy Maintenance with Self-Diagnostic Feature
- Auto Vane & Swing Mode with 3-Notch Fan Speeds
- Auto Restart after Power Failure
- Low Ambient Cooling at -18°C (0°F)
- Factory Installed Ultra-Low Ambient (-40°C/F) Option
- Lead-Lag and Backup Function
- High-Performance Drain Pump (optional)
- Extra-Long Pipe Length - up to 165 ft.
- Refrigerant Pre-Charged
- Easy Installation - No Ductwork Needed
- Weekly Timer - up to 8 Patterns Each Day
- 2-Year Parts Warranty
- 7-Year Compressor Warranty

Indoor Unit Model		Outdoor Unit Model		PKA-A12HA	PKA-A18HA	PKA-A24KA	PKA-A30KA	PKA-A36KA
				PUY-A12NHA3	PUY-A18NHA3	PUY-A24NHA3	PUY-A30NHA3	PUY-A36NHA3
Capacity (Min ~ Max)	Cooling Btu/h			6,000 ~ 12,000	8,000 ~ 18,000	12,000 ~ 24,000	12,000 ~ 30,000	12,000 ~ 34,200
Power Input	Cooling W			1,190	2,240	2,270	4,130	5,030
SEER				15.2	15.3	17.0	15.5	14.0
EER				10.1	8.0	10.6	7.3	6.8
Capacity Control		Variable Compressor Speed						
Refrigerant		R-410A						
Power Supply	V, Phase, Hz	208-230, 1, 60						
Indoor	Dimension (W x D x H)	inch	35 3/8 x 9 1/8 x 11 5/8			46 1/8 x 11 3/8 x 14 3/8		
		mm	898 x 249 x 295			1170 x 295 x 365		
	Weight	lbs (kg)	29 (13)	29 (13)	46 (21)	46 (21)	46 (21)	
	Airflow (Lo-Med-Hi)	CFM Dry	320-370-425	320-370-425	635-705-775	635-705-775	705-810-920	
	Moisture Removal	Pints/h	2.0	5.2	5.0	8.1	9.2	
	Sound (Lo-Med-Hi)	dB(A)	36-40-43	36-40-43	39-42-45	39-42-45	43-46-49	
	Max. Fuse	A	15	15	15	15	15	
	Min. Ampacity	A	1	1	1	1	1	
	Field Drain Pipe Size	I.D. in. (mm)	3/8 (16)	3/8 (16)	3/8 (16)	3/8 (16)	3/8 (16)	
Outdoor	Dimension (W x D x H)	inch	31 1/2 x 13 x 23 3/8			37 3/8 x 13 x 37 1/8		
		mm	800 x 330 x 600			950 x 330 x 943		
	Weight	lbs (kg)	90 (41)	97 (44)	163 (74)	163 (74)	163 (74)	
	Sound	dB(A)	46	46	48	48	48	
	Max. Fuse	A	15	20	30	40	40	
	Min. Ampacity	A	13	13	18	25	25	
Pipe Size	Liq. x Gas in. (mm)	1/2 x 1/2 (6.35 x 12.7)			3/8 x 3/8 (9.52 x 15.88)			
Max. Height Difference	Ft. (m)	100 (30)	100 (30)	100 (30)	100 (30)	100 (30)	100 (30)	
Max. Pipe Length	Ft. (m)	100 (30)	100 (30)	165 (50)	165 (50)	165 (50)	165 (50)	